

Using Least Cost Path Analysis to Plan a New Bypass Route on Highway 401 to Mitigate Traffic Congestion and Impacts in the City of Toronto, Ontario

Kristie Hu and Jonathan Li

EasyChair preprints are intended for rapid dissemination of research results and are integrated with the rest of EasyChair.

May 12, 2023



Using Least Cost Path Analysis to Plan a New Bypass Route on Highway 401 to Mitigate Traffic Congestion and Impacts in the City of Toronto, Ontario

Kristie Hu^{a,*} & Jonathan Li^{a,b}

^a Geospatial Intelligence and Mapping Lab (GIM), University of Waterloo, Kristie Hu - j265hu@uwaterloo.ca ^b Department of Systems Design Engineering, University of Waterloo, Jonathan Li - junli@uwaterloo.ca

* Corresponding author: j265hu@uwaterloo.ca

Keywords: Geographic information system, least cost path analysis, user-defined multiple-criteria evaluation (MCE), network analysis, highway planning

Abstract:

Transit infrastructure development is a major necessity in Canada's largest city and the capital of Ontario, Toronto. As one of the busiest highways in North America and the backbone of Toronto's transportation and distribution system, provincial Highway 401, carries over 416 thousand annual average daily traffic (AADT) and plays an important role in the Ontario southern road network (You et al., 2017). With economic development and ongoing urbanization, the increasing regional population brings up traffic congestion in the system, especially during peak hours. The existing transportation condition has proved a bottleneck under the ongoing globalization & increasing population in the city. To mitigate the congestion, this paper proposed a new bypass route plan on Highway 401 by combining the least cost path analysis (LCPA) and multiple-criteria evaluation (MCE).



Figure 1. The Least Cost Path Analysis Workflow

We used LCPA (Figure 1) as the major solution in the study since it can successfully facilitate informed decision-making in transportation infrastructure planning and design. Moreover, it enables a thorough consideration of various forms of costs in highway construction through multiple criteria cost surfaces to generate the cheapest cost route (Sari & Sen, 2017). The analysis allows for a user-defined solution by allowing a wide range of measures for "cost" through translating and communicating ordinal scales of measure via numeric values. The least cost path analysis has been successfully applied to a wide range of problems in existing research with the most popular application being infrastructure development and design (Bagli et al., 2011).

The primary objective of this research is to apply the least cost path analysis to develop a new bypass route that will divert traffic from regularly congested segments and gridlocks identified on highway 401 in the city of Toronto thereby alleviating traffic congestion and its associated environment, economic and health impacts. Specifically, the key contributions included:



Figure 2. High Congestion Segments on Highway 401

- 1. Identifying a key segment on highway 401 (shown in Figure 2) where the bypass route needs to be introduced along the 401 based on existing traffic congestion trends.
- 2. Defining a set of criteria to be applied to define costs towards generating the least cost path.
- 3. Generating and mapping a cost-effective bypass route on highway 401.
- 4. Quantification of the results of the least cost path analysis and performance assessment through network analysis.

Environmental impacts, land cover types, and slopes were considered during the generation of the LCPA surface while user-defined classes were integrated into the MCE. In Addition, the LCPA+MCE results were quantified and visualized with a series of performance assessments (PA) including buffer analysis (BA) as well as network analysis (NA). The PAs outputs were presented and discussed in the paper to verify whether the use of LCPA+MCE in the decision-making & planning stage would make the model perform better by adapting various real-life MCE facts in this case study.

Acknowledgements

The students Selam Tegenu, Xiliu Yang, Yansong Tu and Yuang Zhang who participated in some parts of the project work are acknowledged.

References

- Bagli, S., Geneletti, D., & Orsi, F. (2011). Routeing of power lines through least-cost path analysis and multicriteria evaluation to minimise environmental impacts. Environmental Impact Assessment Review, 31(3), 234-239.
- Sarı, F., & Şen, M. (2017). Least cost path algorithm design for highway route selection. International Journal of Engineering and Geosciences, 2(1), 1-8.

You, Y., Staebler, M. R., Moussa, G. S., Su, Y., Munoz, T., Stroud, C., Zhang, J., & Moran, D. M. (2017). Long-path measurements of pollutants and micrometeorology over Highway 401 in Toronto. Retrieved from https://www.researchgate.net/profile/Yuan_You4/publication/316704413_Long path_measurements_of_pollutants_and_micrometeorology_over_Highway_401_in_Toronto/links/5a24afa1aca2727 dd87e54f5/Long-path-measurements-of-pollutants-and-micrometeorology-over-Highway-401-in-Toronto.pdf